



MINOS Near Detector

Sacha E. Kopp
University of Texas at Austin

On behalf of...

C. James & J.Thron

Near Detector Installation

P. Shanahan

Near Detector Electronics

D. Harris & H. Montgomery

Near Detector Analysis Group

J. Hylen, S.Kopp, M.Messier

Beam Systematics Analysis Group

P.Anderson, A.Cabrera, G.Drake,
A.Erwin, M. Kordosky, K.Lang,
D.Petyt, H.Ping, D. Reyna,
P.Shanahan, N.Tagg, J.Thomas,
T.Vahle, A.Weber

Calibration Detector

J. Morfin

A Possible New Near Detector



First Role of Near Detector



- Non-ideal focusing requires knowledge of acceptances and pion production in x_F, p_T
- Hadron production variations lead to ~20% variations of predictions in flux.
- This is seen in the flux measured by near detector
- This is the ND's *raison d'être* -- to measure the flux directly and thereby predict far flux




Figure courtesy M. Messier

- Pion production data modeled by
 - Fluka
 - Geant/Fluka
 - MARS
 - BMPT
 - Malensek
 - Sanford/Wang



Differences in Spectra



- The near detector, however, does not exactly reproduce the spectrum at the far detector





Figure courtesy M. Kostin




2nd Role: Commissioning




Can we convince ourselves that we understand our beam during commissioning?

Vary horn currents together



(stat. errors for ~1 day
of Near Detector)





Figures courtesy M. Messier



3rd Role: ν Monitor



- Low E_ν beam flat, hard to monitor relevant parent particles.
- Best way to focus higher energy pions: focus smaller angles.
- Place target on rail system for remote motion capability.
- Horn focusing systematics remain constant \Rightarrow can monitor with this variable beam



Figures courtesy M. Messier




Variable Energy Beam Seen by MINOS Near Detector



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 6

- Also locates neutrino beam
- Lever arm ~ 1040 m
- Neutrino beam center to ~ 10 cm (1 week's data)
- Align ν beam to $10 \mu\text{rad}$
- Requires
 - Special ME/HE run
 - 1 week's data
- See also R.Zwaska's talk on μ Monitors




Figures courtesy D. Harris



Occasional Monitoring


- NuMI low energy beam is *broad*!
 - μ Mon acceptance small at DV end
 - Investigated instrumenting upstream concrete around DV
- Some systematics barely show up
 - Bad: hard to see in monitors
 - Good: not as important for near-to-far extrapolation
- Therefore, some monitoring not as important to do spill-to-spill
 - Periodic monitoring runs sufficient




Figures courtesy D. Harris



4th Role: Study ν Interactions



- Major goal of MINOS is demonstration of dip at $E_\nu \sim 1.8 \text{ GeV}$ and *rise* below this point.
- Neutral currents which mimic CC interactions unfortunately contaminate the low E_ν region.
- Would like to be able to study level of expected NC contamination.








Studying ν Interactions (*cont'd*)



Apparent CC events at $E_{vis} = 2 \text{ GeV}$

	NC events
	CC events

- Possibility of disentangling NC background from real CC events during dedicated running
- Turning off horns removes focusing for pions \Rightarrow less CC events



Figures courtesy D. Harris



Status of Civil Construction



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 10




Near hall





Overview of Installation



- A few months of rack and other infrastructure installation
- Plane installation begins once the electrical portion of the infrastructure is completed
- Electronics cabling and checkout proceeds in parallel with plane installation
- Magnet Coil installation is done after all planes are installed




Infrastructure Installation

Civil Contractor will install

- Water delivery
- Electrical power
- Signal, fiber optic cabling down the MINOS shaft

- After Beneficial Occupancy of the MINOS hall, we install...
- Hall LAN
- ACNET (FNAL accelerator controls)
- Power supply for magnet coil
- Water cooling for electronics






NearDet construction



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 13



Status as of October , 2003

- All planes assembled and “shelved”
- Beneficial occupancy of the Near Hall in Dec’03
- Near detector will be ready late summer 2004



Steel Plane Assembly



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 14





Scintillator Installation




S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 15





Plane Rigging






Plane Installation



- All planes sit in storage at New Muon
- Install planes one-at-a-time, moving from New Muon, to MINOS Service Building, to Underground, to detector support structure in the MINOS Hall





Move planes

From New Muon to MINOS Service Building



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 18

Strongbacks loaded onto truck (shown here without detector planes). Two fit on the Lab's longer flatbed trailer.





Underground Transfer

At the base of the MINOS shaft, a detector plane is transferred from the strongback to a similar fixture on a cart. The strongback never leaves the shaft crane hook.





Mount Planes in Hall



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 20

The cart is rolled into the MINOS Hall, and the plane lifted onto the detector support structure.





M16s and M64s





Far

- 8-fold muxing
- 128 fibers per PMT
- 1452 PMTs



Near

- No muxing
- 64 fibers per PMT
- 210 PMTs



The Eyes of MINOS



Detector Cabling Mock-up



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 22

Set up platform alongside one of the Plane storage stands. Install cabling systems on 2-racks worth of planes.





Tests of Near Det at CERN (CalDet)



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 23

- **MINOS calibration challenge:**

- Near/Far relative calibration to 2%
- absolute calibration of 5%

- **Main ingredients:**

- **cosmic ray muons**

- energy scale calibration
- strip-to-strip response
- muon energy unit (MEU)

- **light injection system**

- PMT gain drifts
- PMT/electronics linearity

- **calibration detector (CalDet)**

- define MEU
- topology and pattern recognition



CalDet modules in T7



On the move... (2003)



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 24



**2001-2003: Moved in/out
beamlines ~10 times**



One reason why everyone loves the CalDet





Front-end electronics comparison: NearDet vs FarDet in CalDet



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 26

- In order to have NearDet and FarDet respond similarly they have to be ... different.


- This is due to scales of the detectors and event rates difference by $\sim 10^5$

- VA + M16 (8x multiplexed)
- QIE + M64 (not multiplexed)


- In 2003 run, each scintillator strip read out on one end by FD electronics, other by ND electronics.

- Compare electronics on same physics hits!

Total MIP, T7 2003 (Run 70771)




Total MIP, Near vs. Far




Very preliminary!!!

P. Vahle, 2003/08/15

Total MIP, Far




Total MIP, Near



Figures courtesy T.Vahle



Near vs Far MIPs






Disentangling Multiple Interaction Spills




- Near detector will see ~10 neutrino interactions per NuMI spill (Far $\ll 1$).
- To disentangle the multiple interactions/spill, near detector employs fast “QIE” electronics developed for KTeV for fast digitization
- Possible to turn up event rate at Caldet to test electronics

Near Detector in NuMI



CalDet at CERN






S-GATE Running



- ND mode for fast spill
 - 10 μ s of continuous data stored in MENU FIFOs
 - Read out after end of spill
- CALDET Mode
 - Most data externally triggered
 - Tests with SGATE mode: led by Dave R.
 - 3% livetime for CALDET, but useful and necessary test of functionality.

>1000 SGATEs/Beam Spill:
9.3 μ s long, separated by 300 μ s



**ND: For 9.3 μ s, ND
FE stores digits for
all RF slices, for all
channels**

**FD: external trigger
enabled during this
time (TOF)**

**PS Beam spill: 400ms, several
times per ~20sec SuperCycle**



S-GATE DATA



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 30

-5 GeV

- **Near Detector**


cum

Oscilloscope:

- **Sum(ADC) vs.
Time in
SGATE**


**One SGATE
9.3 μ s long**

**Each x-bin
is 1 RF slice**






Snarl 47590






Event A






Event B






Event C

Strip
↑






Event D






Event E

Strip
↑








CalDet: electrons



Strip vs. Plane profile, weighted by number of hits







Strip vs. Plane profile, weighted by MEU deposited



Sample Event (2GeV e^+)



Particle response (preliminary)






CalDet – 2 GeV events



S.Kopp -- UT Austin
NBI2003, Tsukuba
Page 39





Additional proposed detector in Near NuMI hall?

Expression of Interest submitted to FNAL PAC

To Perform a High-Statistics (On-Axis) Neutrino
Scattering Experiment using a Fine-grained
Detector in the NuMI Beam

40 Collaborators from

**Argonne - Athens - California/Irvine - Colorado - Duke - Fermilab -
Hampton - IIT - James Madison - Jefferson Lab - MIT -
Minnesota - Pittsburgh - Rutgers - South Carolina - Tufts**


16 Groups: Red = HEP, Blue = NP

Jorge G. Morfin - Fermilab




Survey (pre-K2K) of world's data:

Motivation: Exclusive Cross-sections at Low Energies (1-Pion and Strange Particle): Status - DISMAL



CC

$\nu p \rightarrow \mu^- p \pi^+$



$\nu n \rightarrow \mu^- p \pi^0$

$\nu n \rightarrow \mu^- n \pi^+$

World's sample of NC 1- π

◆ ANL

▼ $\nu p \rightarrow \nu n \pi^+$ (7 events)

▼ $\nu n \rightarrow \nu n \pi^0$ (7 events)

◆ Gargamelle

▼ $\nu p \rightarrow \nu p \pi^0$ (178 evts)

▼ $\nu n \rightarrow \nu n \pi^0$ (139 evts)

◆ K2K

▼ Starting a careful analysis of single π^0 production.

Strange Particle Production

◆ Gargamelle-PS - **15** Λ events.


◆ FNAL 15' \approx 100 events

◆ ZGS - 7 events

◆ BNL - 8 events

A Phased (Installation) High-resolution ν Detector: Basic Conceptual Design

- ◆ 2m x 2 cm x 2cm scintillator (CH) strips with fiber readout. ($\lambda_{\text{int}} = 80$ cm, $X_0 = 44$ cm)
- ◆ **Fiducial volume: ($r = .8\text{m}$ $L = 1.5$ m): 3.1 tons**
R = 1.5 m - p: $\mu = .45$ GeV, $\pi = 51$, K = .86, P = 1.2
R = .75 m - p: $\mu = .29$ GeV, $\pi = 32$, K = .62, P = .93
- ◆ Also 2 cm thick planes of C, Fe and Pb.
 - ▼ 11 planes C = 1.0 ton (+Scintillator)
 - ▼ 3 planes Fe = 1.0 ton (+MINOS)
 - ▼ 2 planes Pb = 1.0 ton
- ◆ Readout: Current concept is VLPC. (How about PMT or CCD + Image Intensifier?)
- ◆ Use MINOS near detector as forward μ identifier / spectrometer.
- ◆ Considering the use of side μ -ID detectors for low-energy μ identification.





UNOFFICIAL Response of the Fermilab PAC to EOI

- ◆ Only **unofficial summary** is currently available! Official letter due in a week or two.
- ◆ We seem to be **“encouraged”** to continue developing the physics, detector and collaboration in order to submit a formal Proposal. How **“encouraged”** will have to wait for the official letter.
- ◆ An indication (**quantitative**) of how these results would **aid** neutrino oscillation experiments would be welcome.
- ◆ **A combined R&D program (multiple EOIs) for detector + readout technology is encouraged.**



Summary



- Near Detector planes are constructed
- Installation schedule now fully developed
 - Begin installation January 2004
 - Complete installation October 2004
- Utility of detector for MINOS is still under study
 - Beam Commissioning
 - Online monitor
 - Neutrino Flux
 - Neutrino reconstruction systematics
- Exciting opportunities to add an additional detector(s) for greater physics reach
 - Collaborators welcome!

- Thanks to Tanaka-san and all for great workshop!